

Amendments to the Claims

1. (Currently Amended) Toothed belt ~~(1)~~ for use with oil and comprising a body ~~(2)~~, a plurality of teeth ~~(4)~~ extending from at least a first surface of said body, said teeth being coated by a first fabric ~~(5)~~, and a plurality of resistant inserts ~~(3)~~;

characterized in that said resistant inserts are produced from at least a first and a second material.

2. (Original) Toothed belt as claimed in claim 1, characterized in that said first material covers said second material at least partly.

3. (Original) Toothed belt as claimed in claim 2, characterized in that said first material entirely surrounds said second material.

4. (Original) Toothed belt as claimed in claim 3, characterized in that said first material has a lower modulus with respect to said second material.

5. (Currently Amended) Toothed belt as claimed in ~~any of~~ claims 1 ~~to 4~~, characterized in that in section said second material occupies a surface between 15 and 75% of the total.

6. (Original) Toothed belt as claimed in claim 5, characterized in that in section said second material occupies a surface between 35 and 45% of the total.

7. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said resistant inserts are of the type known as "Lang's twist".

8. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said first and said second material are chosen in the group constituted by glass fibres, aramid fibres, polyester fibres, PBO fibres and carbon fibres.

9. (Original) Toothed belt as claimed in claim 8, characterized in that said first material is glass fibre.

10. (Currently Amended) Toothed belt as claimed in claim ~~7—or—8~~, characterized in that said second material is carbon fibre

11. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said resistant inserts have been treated with an RFL comprising a latex suitable to resist oils.

12. (Original) Toothed belt as claimed in claim 11, characterized in that said latex comprises an elastomeric material formed from a copolymer obtained from a diene monomer and a monomer containing nitrile groups.

13. (Original) Toothed belt as claimed in claim 12, characterized in that said copolymer is formed from a diene and from a monomer containing nitrile groups in a percentage between 33 and 49 weight % with respect to the final copolymer.

14. (Original) Toothed belt as claimed in claim 13, characterized in that said copolymer is formed from a diene and from a monomer containing nitrile groups in a percentage of 39 weight %.

15. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said fabric (5) is externally coated by a resistant layer (8), which comprises a fluorinated plastomer, a first elastomeric material and a vulcanizing agent; and in that said fluorinated plastomer is present in said resistant layer (8) in an amount greater than said first elastomeric material.

16. (Currently Amended) Toothed belt as claimed in claim 15, characterized in that said body (2) comprises a mixture based on a second elastomeric material formed from a copolymer obtained from a diene monomer and a monomer containing nitrile groups.

17. (Currently Amended) Toothed belt as claimed in claim 15 ~~or 16~~, characterized in that said resistant layer (8) comprises said fluorinated plastomer in an amount in weight between 101 and 150 parts in weight with respect to said elastomeric material.

18. (Currently Amended) Toothed belt as claimed in ~~any of claims 15 to 17~~, characterized in that said fluorinated plastomer is polytetrafluoroethylene.

19. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that the back (6) of said belt is covered by a second fabric (7).

20. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said second fabric (7) is externally coated by a second resistant layer (8).

21. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that said second resistant layer ~~(8)~~ is the same as said first resistant layer.

22. (Currently Amended) Toothed belt as claimed in ~~any of claims 15 to 21~~, characterized in that said elastomeric material comprises fibres.

23. (Original) Toothed belt as claimed in claim 22, characterized in that said fibres are present in an amount in weight between 0.5 and 15% with respect to said elastomeric material.

24. (Currently Amended) Toothed belt as claimed in ~~any one of the previous~~ claims 1, characterized in that it comprises between the toothing ~~(4)~~ and said back ~~(6)~~ sides treated with a polymer resistant to swelling.

25. (Currently Amended) Timing control system for a drive motor vehicle comprising at least a driving pulley, a driven pulley and a toothed belt ~~(1)~~ for use with oil and comprising a body ~~(2)~~, a plurality of teeth ~~(4)~~ extending from at least a first surface of said body, said teeth being covered by a first fabric ~~(5)~~, and a plurality of resistant inserts ~~(3)~~, characterized in that said toothed belt is produced according to ~~any one of claims 1 to 24~~.

26. (Currently Amended) Control system as claimed in claim 25, characterized in that it comprises a pad tensioner ~~(34)~~ or a pad ~~(35)~~.